Microwaves & RF 2001 Editorial Index

COMMERCIAL

- PCB prototypes give hint of emerging MMW applications *(January, p. 127)*
- Tracing the history of an industry *(October, p. 31)*

COMMUNICATIONS

- Comparing infrared and Bluetooth short-range solutions *(January, p. 121)*
- Startup shaves phase noise from microwave sources *(January, p. 156)*
- Fiber-optic technology drives to 10 Gb/s and beyond *(February, p. 29)*
- Adding GPS to CDMA mobile-telephone handsets *(March, p. 69)*
- Suppress AM in GSM direct-conversion receivers *(March, p. 83)*

COMPONENTS

- Understand the basics of microstrip directional couplers *(January, p. 79)*
- Design a very-wide-range VCO *(January, p. 95)*
- Stainless-steel semirigid cables handle hostile environments *(February, p. 152)*
- Linear LNAs boast miniscule noise figures at 2 GHz *(February, p. 162)*
- Linear amplifier powers 2.4-GHz WLAN applications *(March Cover, p. 147)*
- Theory enables locking-band widening of injection-locked IMPATT oscillators, Part 1 *(April, p. 86)*
- Design an equal-element lowpass filter *(April, p. 99)*
- SAWs stabilize low-phase-noise voltage-tuned sources *(April Cover, p. 115)*
- Design a tunable resonant-tank circuit *(May, p. 69)*
- Theory enables locking-band widening of injection-locked IMPATT oscillators, Part 2 *(May, p. 95)*
- Diminutive splitter channels 5 to 1000 MHz *(May Cover, p. 123)*
- Design a tunable resonant-tank circuit *(June, p. 73)*
- Design high-order PLLs *(July, p. 69)*
- MEMS technology moves increasingly toward microwave applications *(July, p. 97)*
- YROs combine wide band with high speed *(July, p. 122)*
- CMOS SOS switches offer useful features, high integration *(August, p. 107)*
- Parameter describes mixer IM performance *(August, p. 127)*

- Design a low-noise synthesizer using YRO technology *(August, p. 133)*
- Wideband VCO designs are independent of circuit parameters *(August, p. 147)*
- PLLs shine with sapphire technology *(August, p. 196)*
- SAW filter screens GPS receive signals *(August, p. 199)*
- Comparing integer-N and fractional-N synthesizers *(September, p. 93)*
- Specifying microwave voltage-controlled oscillators *(September, p. 107)*
- Bias tee and DC block illuminate 65 GHz *(September Cover, p. 116)*
- Linear HBT amplifiers arrive from new source *(September, p. 124)*
- Adapter makes blindmate connections to 40 GHz *(September, p. 125)*
- Practical guidelines target LNA design *(October, p. 106)*
- Multilayer magic yields shrinking circuits *(October, p. 117)*
- Low-cost design kit boasts 90 HBT amps *(October, p. 120)*
- MEMS animates miniature RF switch *(November, p. 104)*

COMPUTER-AIDED ENGINEERING

- EDA tool relates EVM to a filter's group delay *(January, p. 73)*
- Simulation method identifies multipath tracking errors *(February, p. 55)*
- Webwatch section *(March, p. 131)*
- EM software receives major enhancements *(April, p. 135)*
- Models aid the analysis of electronics cooling *(June, p. 95)*
- Upgraded SPICE package soars with new features *(June, p. 107)*
- Program performs filter calculations *(June, p. 110)*
- Math package boasts host of improvements *(June, p. 115)*
- Software speeds creation of circuit layouts *(June, p. 117)*
- Enhancements grace free EM simulator *(June, p. 129)*
- Emulator mimics mobile communication channels *(July, p. 61)*
- EDA software improves accuracy of microstrip filter designs *(August, p. 122)*
- Simulator tackles tricky EM problems *(August, p. 200)*
- SPICE-based software fine-tunes designs *(August, p. 204)*
- Simulation tool models and verifies timing jitter in oscillators *(September, p. 65)*
- VHDL approach improves harmonic-balance simulation *(November, p. 76)*

CONFERENCES

- Event showcases products for Bluetooth® developers *(February, p. 127)*
- Symposium conference sessions mirror industry's expansion *(March, p. 33)*
- Wireless Symposium heralds new era in communications *(March, p. 39)*
- Measurement group tackles telecom testing accuracy *(March, p. 51)*
- Conference unites military designers *(April, p. 29)*
- 27th annual RF & Hyper Meeting highlights new products *(April, p. 35)*
- Optics shine on brightly at OFC *(May, p. 31)*
- MTT-S section *(May, p. 106)*
- ARMMS meeting melds simulation and testing *(August, p. 59)*
- Tenth annual Wireless Show is renamed and revamped *(December, p. 29)*

CROSSTALK

- Dr. K. "Ram" Ramachandran, President of Filtran Microcircuits *(April, p. 43)*
- Dr. Zoltan Cendes, Chairman and CEO of Ansoft Corp. *(September, p. 47)*

DEFENSE ELECTRONICS

- Automated process cuts filter tuning time from hours to minutes *(June, p. 103)*
- Facing warfare in the third millennium *(September, p. 31)*

DEVICES & ICs

- Semiconductors vie for space in wireless systems *(January, p. 31)*

Focus microwaves

Prematching Tuner
High power, 0.8 - 7 GHz

superior technology

Harmonic Load Pull System 1.8 - 18 GHz
Compact, user friendly operation

Experience the cutting-edge precision and *state of the art* features included in every Focus product:

- Prematching* and Harmonic* coaxial tuners, *0.2 - 50 (65) GHz*
- Fundamental waveguide tuners, *26.5 - 110 GHz*
- Advanced Load Pull and Noise measurement software
- VNA TRL calkits, *0.1 - 50 GHz*
- Manual tuners (with prematching options), *0.4 - 50 GHz*
- Modular, low loss, high power test fixtures*

* *US patents pending*

Harmonic Source & L/P Software
Intuitive operation with unique options

Focus Microwaves offers complete measurement solutions for high power, harmonic & noise testing; on-wafer or in fixture. *Over 400 systems in operation worldwide.*

L/P Tuners, TRL Calkit & Transistor Test Fixture
A complete measurement solution

Phone: +1.514.335.6227 Fax: +1.514.335.6287
www.focus-microwaves.com

Visit us at Wireless Systems 2002 Booth #1246
Enter No. 205 at www.mwrf.com

- A primer on using PIN diodes in VCAs *(January, p. 57)*
- More power per transistor translates into smaller amplifiers *(January, p. 132)*
- InGaP HBTs promise long operating lifetimes *(January, p. 146)*
- Model, analyze, and simulate $\Sigma\Delta$ fractional-N frequency synthesizers *(January, p. 150)*
- A primer on using PIN diodes in VCAs *(February, p. 99)*
- Transceiver MCMs fuel 3G wireless systems *(February Cover, p. 136)*
- Single-chip transmitters include microcontroller and memory *(February, p. 150)*
- RF IC addresses unlicensed 5-GHz communications *(February, p. 157)*
- Transceiver chip set integrates triband GSM functions *(March, p. 153)*
- Radio IC cuts costs of building 2.4-GHz WLANs *(March, p. 157)*
- Radio chip set arms 5-GHz, 54-Mb/s wireless networks *(March, p. 163)*
- E-PHEMT promises high linearity from a single supply *(April, p. 137)*
- Single CMOS chip completes Bluetooth system *(April, p. 139)*
- Compact receive module shrinks CDMA circuits *(May Cover, p. 155)*
- Micro-X amps provide cascadable gain to 8 GHz *(May, p. 165)*
- Direct-conversion IC fits GSM needs *(May, p. 171)*
- FM transceivers connect short-range applications *(May, p. 174)*
- Cell-pack RF ICs simplify communications design *(May, p. 179)*
- Reviewing the basics of MMIC design *(June, p. 55)*
- Radio chip sets power millimeter-wave systems *(June, p. 131)*
- Low-power IC packs GPS receiver *(July, p. 118)*
- Radio chip sets power millimeter-wave systems *(July, p. 127)*
- LDMOS delivers 500 W for IFF systems *(August, p. 185)*
- Selecting prescalers for PLL synthesizers *(September, p. 102)*
- SiGe direct modulators drive BTS designs to 4 GHz *(October, p. 113)*
- Process enhancements spark semiconductor advances *(November, p. 31)*
- Miniscule module tracks 12 GPS channels *(November, p. 103)*
- SiGe tuner targets advanced set-top boxes *(November, p. 106)*
- Weigh amplifier dynamic-range requirements *(December, p. 59)*
- Linear amp powers 80 W for MMDS applications *(December, p. 71)*
- Amplifier drives Bluetooth and wireless data *(December, p. 103)*
- Low-power IF IC digitizes 300 MHz *(December Cover, p. 106)*
- HBT amplifiers boast adaptive bias control *(December, p. 120)*

MATERIALS

- Selecting a shielding supplier *(January, p. 109)*
- Compact router speeds prototype PCB development *(January, p. 115)*
- Selecting a shielding supplier *(February, p. 123)*

SYSTEMS & SUBSYSTEMS

- Slotted-line system measures S-parameters automatically *(January, p. 101)*
- Raise bandwidth efficiency with sine-wave-modulation VMSK *(April, p. 79)*
- Low-cost manufacturing holds the key to LMDS success *(May, p. 59)*
- LMDS backers seek low-cost solutions *(June, p. 33)*
- Link balancers extend cellular-receiver range *(July, p. 123)*
- Construct an FMCW front end for anticollision radar *(August, p. 97)*
- RF subsystem enables cable telephony *(August, p. 193)*
- System speeds assembly of RF power devices *(August, p. 203)*
- Design of short-range radio systems *(September, p. 73)*
- System boosts amplifier test-set dynamic range *(September, p. 120)*
- Effective efficiency is a new approach to Tx design *(October, p. 57)*
- Understanding regulations for short-range radios *(October, p. 79)*
- Noncoherent detection improves FQPSK system performance *(November, p. 55)*
- Considering antenna options for LMDS *(November, p. 65)*

- Interpret and apply EVM to RF system design *(December, p. 83)*
- Uncover Bluetooth packet errors *(December, p. 96)*

TEST & MEASUREMENT

- Calculate oscillator jitter by using phase-noise analysis *(January, p. 82)*
- Broadband synthesizer trims phase noise through 40 GHz *(January Cover, p. 141)*
- Evaluate noise in GSM PAs *(February, p. 69)*
- Clarify antenna gain for accurate mobile measurements *(February, p. 103)*
- Calculate oscillator jitter by using phase-noise analysis *(February, p. 109)*
- Testset records and analyzes Bluetooth signals *(February, p. 148)*
- Simple instrument offers accurate Bluetooth communications testing *(February, p. 154)*
- Software-based monitoring system checks digital carriers *(February, p. 158)*
- Probe on-wafer diodes *(March, p. 91)*
- Waveguide irregularities impair VNA millimeter-wave measurements *(March, p. 97)*
- Consider load tolerance in amplifiers for immunity/susceptibility *(March, p. 111)*
- Understanding single-ended and mixed-mode S-parameters *(March, p. 121)*
- Synthesizers shave noise in receivers and test equipment *(March, p. 166)*
- Waveform generator creates complex modulation formats *(March, p. 171)*
- Multi-tone generators streamline communications testing *(April, p. 63)*
- Scrutinizing single-ended S-parameters *(April, p. 109)*
- Device measures gain and phase from 0.1 to 2.7 GHz *(April, p. 123)*
- Impedance analyzer reaches 3 GHz *(April, p. 125)*
- Wideband analyzer checks multichannel propagation *(April, p. 129)*
- Instrument combines counter, power meter, and digital voltmeter *(April, p. 130)*
- Low-noise synthesizer switches across dual ranges *(April, p. 132)*
- Synthesizers stop degradation from phase hits *(April, p. 141)*
- Understanding ACPR measurements *(May, p. 91)*
- Grasp the meaning of mixed-mode S-parameters *(May, p. 99)*
- Low-noise synthesizers aid broadband testing *(May, p. 167)*
- Test systems offer CDMA solutions *(May, p. 176)*
- Making ACPR measurements *(June, p. 79)*
- Performing S-parameter measurements *(June, p. 99)*
- Personal monitor checks RF safety levels *(June, p. 128)*
- Fast synthesizer races from 4.5 to 6010 MHz *(June, p. 133)*
- T&M firms forge ahead despite the communications slump *(July, p. 35)*
- Test RF equipment with an isolated T capacitive coupler *(July, p. 89)*
- Harmonic tuners support accurate load-pull testing *(July, p. 107)*
- Modern signal generators emulate complex waveforms *(July, p. 111)*
- Switch aids microwave testing *(July, p. 129)*
- Group-delay option enhances microwave analyzer *(July, p. 130)*
- Silicon MMIC amplifier boasts low noise figure *(July, p. 131)*
- Garage gives birth to measurement giant *(August, p. 35)*
- Simulate IMD in RF amplifiers with memory effects *(August, p. 85)*
- Use a sampling power meter to determine the characteristics of RF and microwave devices *(September, p. 81)*
- Jitter analyzers help solve timing problems *(September, p. 126)*
- Use a sampling power meter to determine the characteristics of RF and microwave devices *(October, p. 97)*
- Vector signal generator keeps pace with 3G *(October, p. 98)*
- Spectrum analyzers simplify 3G measurements *(October, p. 121)*
- Agile synthesizer reaches 6.4 GHz *(November Cover, p. 92)*
- Vector analyzers tackle differential measurements *(December, p. 125)*